

LTC4274 Single Port IEEE802.3at PSE

DESCRIPTION

Demonstration circuit 1567B features the [LTC®4274](#), a single power sourcing equipment (PSE) controller designed for use in IEEE 802.3 Type 1 and Type 2 (high power) compliant Power over Ethernet (PoE) systems. The LTC4274 is configured in the DC1567B as a midspan power injector where data comes in from an existing network system and out, along with power, to a powered device (PD). The LTC4274 autonomously detects and classifies a PD, turns power on to the port, and disconnects port power without the need for a microcontroller. A two second backoff timer supports the midspan configuration.

Only a single 55V supply is required to power the DC1567B. A simple regulator circuit on the board powers the digital supply of the LTC4274.


The LTC4274 delivers low heat dissipation by utilizing a low R_{ON} external MOSFET and a 0.25Ω sense resistor, eliminating the need for expensive heat sinks. An external MOSFET also provide a more robust solution compared to an integrated MOSFET.

Power controlled by the LTC4274 is connected to the center taps on the cable side of the Ethernet transformers for data pairs 4/5 and 7/8. An integrated RJ45 connector includes the Ethernet transformer, common mode termination, and LEDs. One LED is also controlled by the LTC4274 to indicate the port is powered. Test turrets provide test points for port power measurements.

The DC1567B has increased surge protection from the DC1567A. The DC1567B is Ethernet Alliance™ certified.

[Design files for this circuit board are available.](#)

All registered trademarks and trademarks are the property of their respective owners.



DEMO MANUAL DC1567B

TYPICAL PERFORMANCE

Table 1. Typical DC1567B Performance Summary ($T_A = 25^\circ\text{C}$)

PARAMETER	CONDITION	VALUE
Input Voltage	GND – V_{EE} , Typical Voltage, IEEE Type 1 and Type 2 Complaint Output	51V to 57V
V_{DD} Supply Voltage	$V_{DD} - DGND$, Generated on Demo Board from V_{EE}	3.4V to 3.8V
Powered Pairs	PoE Power at RJ45 Connector	Alternative-B (Positive on Pins 4/5, Negative on 7/8)
PSE Operation Mode	AUTO Pin Logic High	IEEE802.3at Mode
Midspan Backoff	MID Pin Logic High, Backoff Time After Detection	2.5s
Detection Type	25k Signature Detection	4-Point PD Detection
	Class 4	2-Event Classification
RJ45 Amber LED Indicator	PD Detected and Port Power is On	LED On
	Port Power is Off	LED Off
Port Output Voltage	$V_{EE} = -55.0\text{V}$, $R_{SENSE} = 0.25\Omega$, MOSFET = PHT6NQ10T, Port Load = 600mA, $V_{PORT+} - V_{PORT-}$	-54.7V
Disconnect Current	DC Disconnect, Maintain Power Signature, Typical Disconnect Current at the Port for 350ms, $R_{SENSE} = 0.25\Omega$	<7.8mA
AUTO Pin High Mode Overcurrent Sense	$R_{SENSE} = 0.25\Omega$, Class 0 or Class 3	376mA
	$R_{SENSE} = 0.25\Omega$, Class 1	112mA
	$R_{SENSE} = 0.25\Omega$, Class 2	208mA
	$R_{SENSE} = 0.25\Omega$, Class 4	636mA

QUICK START PROCEDURE (Figure 1)

1. Connect a 55V power supply across AGND and V_{EE} as shown in Figure 1.
2. Connect probes across VPORT+ and VPORT- for measurements.
3. Connect with a CAT5 cable to a PD at J1.
4. Connect a PHY with a CAT5 cable to J2 for data testing (optional).




Figure 1. DC1567B Setup

OPERATION

DC1567B provides a simple single port IEEE 802.3at Type 1 and Type 2 PSE solution with the LTC4274. It runs fully autonomously and only requires a supply at V_{EE} . Detection, classification, port power on and disconnect is all performed without the need of a microcontroller. The voltage drop to the port is minimized with the LTC4274 solution because of the low R_{ON} external MOSFET and a 0.25Ω sense resistor, thus reducing power consumption.

Input Supply

IEEE 802.3at requires that a Type 2 PSE output at the port between 50V to 57V. To meet this requirement, it is recommended to supply a nominal 55V across AGND and V_{EE} on the DC1567B as shown in Figure 1. Main PS LED indicates the input power supply is powering the LTC4274.

V_{DD} Supply

DC1567B generates a V_{DD} supply from V_{EE} using just three components allowing for V_{EE} to be the only required supply. V_{DD} is tied to AGND and DGND is a negative voltage below AGND.

AUTO Pin High Mode

The AUTO pin on the LTC4274 is tied logic high on the DC1567B to set the device to AUTO pin high mode. In AUTO pin high mode, the LTC4274 autonomously detects, classifies, powers on a valid detected PD, and disconnects power to the port when the PD is removed. An LED in the integrated RJ45 connector displays if the port is powered.

Midspan

The LTC4274 on the DC1567B, the MID pin is tied logic high to set the device to midspan mode. In midspan mode, port detection occurs every midspan backoff time of 2.5s.

Detection and Classification

The LTC4274 performs 4-point PD detection with 2-point forced voltage and 2-point forced current for higher reliability of valid PD detection. Once a valid PD is detected, classification is carried out. The LTC4274 in AUTO pin high mode detects and classifies class 0 through class 4 PDs and sets the port current limits according to the PD class. In the event a class 4 is detected, the LTC4274 outputs a 2-Event classification to signal to the PD that it is a valid IEEE 802.3at PSE and can supply the high power.

Disconnect

The LTC4274 performs DC disconnect. In order for a PD to remain on, it must display a maintain power signature by drawing more than 10mA. If the port load is less than 5mA for 350ms (typ), then the LTC4274 will remove power from the port.

Overcurrent

The LTC4274 in AUTO pin high mode detects, classifies and sets the current limits according to the classification results. Refer to Table 1 for the overcurrent limits with a 0.25Ω sense resistor.

\overline{SHDN} and \overline{RESET} Pushbuttons

The DC1567B has pushbuttons to the LTC4274 \overline{SHDN} , \overline{RESET} and DGND pins. Momentarily tying \overline{SHDN} to DGND will shut down the port if it is on and disable detection preventing the port from turning on again. Momentarily tying \overline{RESET} to DGND will reset the LTC4274 to its AUTO pin high mode state without having to cycle power.

SURGE PROTECTION

Ethernet ports can be subject to significant cable surge events. To keep PoE voltages below a safe level and protect the application against damage, protection components are required at the main supply, at the LTC4274 supply pins and at the port.


Bulk transient voltage suppression devices and bulk capacitance are required across the main PoE supply and should be sized to accommodate system level surge requirements. The DC1567B diode D2 and capacitor C2 are example components for this protection at the main PoE supply.

The LTC4274 requires a 10Ω , 0805 resistor (R10) in series from supply AGND to the LTC4274 AGND pin. Across the LTC4274 AGND pin and V_{EE} pin are an SMAJ58A, 58V TVS (D3) and a $1\mu\text{F}$, 100V bypass capacitor (C4). These components must be placed close to the LTC4266 pins.


The port requires a pair of S1B clamp diodes: one from OUT to supply AGND and one from OUT to supply V_{EE} . The diodes at the ports steer harmful surges into the supply rails where they are absorbed by the surge suppressors and the V_{EE} bypass capacitance. The layout of these paths must be low impedance.

PCB LAYOUT AND FILM

Top Assembly




Top Side




PCB LAYOUT AND FILM

Inner Layer 2




Inner Layer 3




PCB LAYOUT AND FILM

Bottom Side



Assembly Bottom





ESD Caution

ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

Legal Terms and Conditions

By using the evaluation board discussed herein (together with any tools, components documentation or support materials, the "Evaluation Board"), you are agreeing to be bound by the terms and conditions set forth below ("Agreement") unless you have purchased the Evaluation Board, in which case the Analog Devices Standard Terms and Conditions of Sale shall govern. Do not use the Evaluation Board until you have read and agreed to the Agreement. Your use of the Evaluation Board shall signify your acceptance of the Agreement. This Agreement is made by and between you ("Customer") and Analog Devices, Inc. ("ADI"), with its principal place of business at One Technology Way, Norwood, MA 02062, USA. Subject to the terms and conditions of the Agreement, ADI hereby grants to Customer a free, limited, personal, temporary, non-exclusive, non-sublicensable, non-transferable license to use the Evaluation Board FOR EVALUATION PURPOSES ONLY. Customer understands and agrees that the Evaluation Board is provided for the sole and exclusive purpose referenced above, and agrees not to use the Evaluation Board for any other purpose. Furthermore, the license granted is expressly made subject to the following additional limitations: Customer shall not (i) rent, lease, display, sell, transfer, assign, sublicense, or distribute the Evaluation Board; and (ii) permit any Third Party to access the Evaluation Board. As used herein, the term "Third Party" includes any entity other than ADI, Customer, their employees, affiliates and in-house consultants. The Evaluation Board is NOT sold to Customer; all rights not expressly granted herein, including ownership of the Evaluation Board, are reserved by ADI. CONFIDENTIALITY. This Agreement and the Evaluation Board shall all be considered the confidential and proprietary information of ADI. Customer may not disclose or transfer any portion of the Evaluation Board to any other party for any reason. Upon discontinuation of use of the Evaluation Board or termination of this Agreement, Customer agrees to promptly return the Evaluation Board to ADI. ADDITIONAL RESTRICTIONS. Customer may not disassemble, decompile or reverse engineer chips on the Evaluation Board. Customer shall inform ADI of any occurred damages or any modifications or alterations it makes to the Evaluation Board, including but not limited to soldering or any other activity that affects the material content of the Evaluation Board. Modifications to the Evaluation Board must comply with applicable law, including but not limited to the RoHS Directive. TERMINATION. ADI may terminate this Agreement at any time upon giving written notice to Customer. Customer agrees to return to ADI the Evaluation Board at that time. LIMITATION OF LIABILITY. THE EVALUATION BOARD PROVIDED HEREUNDER IS PROVIDED "AS IS" AND ADI MAKES NO WARRANTIES OR REPRESENTATIONS OF ANY KIND WITH RESPECT TO IT. ADI SPECIFICALLY DISCLAIMS ANY REPRESENTATIONS, ENDORSEMENTS, GUARANTEES, OR WARRANTIES, EXPRESS OR IMPLIED, RELATED TO THE EVALUATION BOARD INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, TITLE, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. IN NO EVENT WILL ADI AND ITS LICENSORS BE LIABLE FOR ANY INCIDENTAL, SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES RESULTING FROM CUSTOMER'S POSSESSION OR USE OF THE EVALUATION BOARD, INCLUDING BUT NOT LIMITED TO LOST PROFITS, DELAY COSTS, LABOR COSTS OR LOSS OF GOODWILL. ADI'S TOTAL LIABILITY FROM ANY AND ALL CAUSES SHALL BE LIMITED TO THE AMOUNT OF ONE HUNDRED US DOLLARS (\$100.00). EXPORT. Customer agrees that it will not directly or indirectly export the Evaluation Board to another country, and that it will comply with all applicable United States federal laws and regulations relating to exports. GOVERNING LAW. This Agreement shall be governed by and construed in accordance with the substantive laws of the Commonwealth of Massachusetts (excluding conflict of law rules). Any legal action regarding this Agreement will be heard in the state or federal courts having jurisdiction in Suffolk County, Massachusetts, and Customer hereby submits to the personal jurisdiction and venue of such courts. The United Nations Convention on Contracts for the International Sale of Goods shall not apply to this Agreement and is expressly disclaimed.