

Features

- Solid-state Silicon technology
- Low Capacitance
- Low Clamping Voltage
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)


Maximum Ratings

- Operating Junction Temperature Range: -55°C to +125°C
- Storage Temperature Range: -55°C to +150°C

MCC Part Number	Device Marking
SRV05-4D	1208 5U


IEC61000-4-2(ESD)	Air Contact	±30KV ±30KV
Peak Pulse Current(8/20µs)	I _{PP}	6A
Peak Pulse Power (8/20µs)	P _{PK}	72W

Internal Structure



**Snap Back
ESD Protection
Device**

SOT23-6L



DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.012	0.020	0.30	0.50	
B	0.051	0.070	1.30	1.80	
C	0.087	0.126	2.20	3.20	
D	0.037		0.95		TYP.
G	0.074		1.90		TYP.
H	0.106	0.122	2.70	3.10	
J	0.002	0.006	0.05	0.15	
K	0.030	0.051	0.75	1.30	
L	0.012	0.024	0.30	0.60	
M	0.003	0.008	0.08	0.22	

Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
I/O Pins						
Reverse Working Voltage	V_{RWM}				5	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	7	8	9	V
Reverse Leakage Current	I_R	$V_{RWM}=5V$		<1	100	nA
Forward Voltage	V_F	$I_F = 10mA$	0.6	0.9	1.2	V
Clamping Voltage ^(Note 1)	V_C	$I_{PP}=16A, t_p=100ns$		11		V
Dynamic Resistance ^(Note 1)	R_{DYN}			0.31		Ω
Clamping Voltage ^(Note 2)	V_C	$V_{ESD}=8KV$		12		V
Clamping Voltage ^(Note 3)	V_C	$I_{PP}=1A, t_p=8/20\mu s$		6.6	8	V
Clamping Voltage ^(Note 3)	V_C	$I_{PP}=6A, t_p=8/20\mu s$		10	12	V
Junction Capacitance	C_J	$V_R=0V, f=1MHz,$ Any I/O pin to GND		1.2	1.6	pF
Junction Capacitance	C_J	$V_R=0V, f=1MHz,$ Between any I/O pins		0.6	0.8	pF
VDD Pins						
Reverse Working Voltage	V_{RWM}				6	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR}=1mA$	7	8	9	V
Reverse Leakage Current	I_R	$V_{RWM}=6V$			1	μA
Forward Voltage	V_F	$I_F = 10mA$	0.6	0.9	1.2	V
Clamping Voltage ^(Note 1)	V_C	$I_{PP}=16A, t_p=100ns$		9.5		V
Dynamic Resistance ^(Note 1)	R_{DYN}	$t_p=100ns$		0.2		Ω
Clamping Voltage ^(Note 2)	V_C	$V_{ESD}=8KV$		10		V
Clamping Voltage	V_C	$I_{PP}=1A, t_p=8/20\mu s$		6.4	7	V
Clamping Voltage	V_C	$I_{PP}=9A, t_p=8/20\mu s$		9.5	11	V

Note:

1. TLP Parameter: $Z_0=50\Omega, t_p=100ns, t_r=2ns,$ Averaging Window from 60ns to 80ns. RDYN is Calculated from 4A to 16A.
2. Contact Discharge Mode, According to IEC61000-4-2.
3. Non-repetitive Current Pulse, According to IEC61000-4-5.

Curve Characteristics

Fig. 1 - 8 X 20 μ s Pulse Waveform




Fig. 2 - Non-Repetitive Peak Pulse Power



Fig. H- Capacitance Characteristics




Fig. 4 - Clamping Voltage Characteristics




Fig. 5 - Pulse Derating Curve






Fig. 6 - TLP Measurement - I/O to GND



Curve Characteristics

Fig. 1 - TLP Measurement - VDD to GND



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note : Adding "-HF" Suffix for Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp**. products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.