## XBH1AA0G4

Harmony XB5, Digital panel meter, plastic, black, Ø22, 4 digit green LED display, 4...20 mA input



#### Main

Range of Product	Harmony XB5
Product or Component Type	Display module
Display digits	4 - 0.55 in (14 mm)

Complementary

Complementary	
Display Type	7 segments LED
Display colour	Green
Display projection	-9999999
Accuracy	+/- 0.15 % of the measuring range
Solid state output type	2 x power MOSFET
Discrete output voltage	30 V DC
Discrete output current	0.5 A
Brightness	Fixed
Analogue input range	420 mA DC
Maximum voltage drop	6 V
Temperature drift	50 ppm/°C
Mounting diameter	0.89 in (22.5 mm)
Connections - terminals	Spring terminals, 1 x 0.21 mm² AWG 24AWG 17)
Housing material	Plastic
Flame Retardance	UL94-V1
Tightening torque	1.3 N.m 11.5 lb.in
Width	2.03 in (51.5 mm)
Height	1.16 in (29.5 mm)
Depth	3.08 in (78.2 mm)
Net Weight	0.07 lb(US) (0.032 kg)

#### **Environment**

Ambient air temperature for operation	-4140 °F (-2060 °C)	
Ambient Air Temperature for Storage	-4185 °F (-2085 °C)	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	
IP degree of protection	IP65 IEC 60529 front panel)	
Standards	EN 61326-1	

## Ordering and shipping details

Category	22467 - PUSHBUTTONS,22MM(PLASTIC) NEW
Discount Schedule	CS2
GTIN	3606489737214
Nbr. of units in pkg.	1
Package weight(Lbs)	2.40 oz (68 g)
Returnability	Yes
Country of origin	FR


## Packing Units

PCE
1.50 in (3.8 cm)
3.35 in (8.5 cm)
5.04 in (12.8 cm)
S03
62
10.60 lb(US) (4.807 kg)
11.81 in (30 cm)
11.81 in (30 cm)
15.75 in (40 cm)

# Product data sheet Dimensions Drawings

# XBH1AA0G4

#### **Dimensions**



e: Clamping thickness 1 to 6 mm

(1): Side view(2): Front view

# Product data sheet Mounting and Clearance

# XBH1AA0G4

### Mounting and Clearance

## Panel Cut-out for Digital Display

